

LogiLink_®


HDMI[™] Switch, 3x1 Ports 1080p/60 Hz, Remote Control

Art. No.: HD0042

Designed for applications that require the routing of 3 sources to 1 compatible display device. It enables the reliable transmission at video resolutions up to 1080p@60 Hz. Features auto and manual switching modes for selection; instantly switching for a smooth video transition between HDMI ports.

Features:

- » Allows up to three HDMI sources to be connected to one HDMI display
- » Supports manual switching, remote switching or automatic switching
- » Resolution up to Full HD 1080p@60 Hz
- » Bandwidth up to 7.5 Gbps (2.5 Gbps at 250 MHz per channel)
- » Supports 3D and HDCP pass-through
- » Supports Consumer Electronics Control (CEC)
- » Supports 36 bit Deep Color (12 bit per channel)
- » Supports LPCM 7.1, Dolby TrueHD and DTS-HD Master Audio™
- » Perfect solution for home, schools, bars and restaurants



*The specifications and pictures are subject to change without prior notice *All trade names referenced are the registered trademarks of their respective owners. IR Receiver

Specifications:

| Input (Source) | 3x HDMI-A female, 1x 3.5 mm jack for IR |
|------------------------------------|--|
| Output (Display) | 1x HDMI-A female |
| HDMI Standard | 1.3 |
| HDCP | Pass through |
| Output Resolution | 480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz |
| CEC (Consumer Electronics Control) | Yes |
| DDC (Display Data Channel) | Yes |
| 3D Supporting | Yes |
| Video Bandwith | Up to 7.5 Gbps |
| TMDS | Yes |
| Max. TMDS Character Rate | 250 MHz |
| Max. Data Rate | 6 Gbps |
| Data Channels | 3 |
| Color Format Support | RGB/YCbCr4:4:4/YCbCr4:2:2 |
| Color Depth Support | 12 bit |
| Switch | Select button |
| Uncompressed Audio | LPCM 7.1 |
| Compressed Audio | DTS-HD Master Audio™, Dolby TrueHD |
| Standby Power Consumption | 0.5 W |
| Power Supply | HDMI bus powered |
| Hot Plug and Plug & Play | Yes |
| LED Indication | Yes |
| IR Remote Control | Yes |
| Remote Control Battery | 1x CR2025 |
| Working Distance of Remote | Up to 5 m |
| Chassis Material | ABS |
| Color | Black |
| Operating Temperature | 0–70°C |
| Operating Humidity | 10–85% RH (no condensation) |
| Dimensions | 8 x 5.8 x 1.8 cm |
| Weight | 54 g |
| | |

Package Contents:

- » 1x HDMI Switch
- » 1x Remote Control
- » 1x IR Receiver
- » 1x User Manual

Package Information:

- » Packing Dimension: 160 x 107 x 50 mm
- » Packing Weight: 0.16 kg
- » Carton Dimension: 575 x 255 x 345 mm
- » Carton Q'ty: 40 pcs
- » Carton Weight: 7.2 kg



