

## TECHNICAL DATA SHEET

### ADHESIVE TAPE: MSK LOW TACK

**Product Description:** Masking self-adhesive tape of low adhesion strength is very convenient for long term protection of smooth surfaces (glass, Aluminium, plastic, plaster, wall paper, cork, painted surfaces). No adhesive residue is left after removal for up to 15 days without leaving any traces or residues. For indoor or outdoor application. Acrylic adhesive without harmful solvents.

Technical Data	Unit	Result
Support Colour		VIOLET
Support weight	g/m <sup>2</sup>	55
Total thickness	µm	105
Tensile Strength	N/cm	40
Elongation	%	8
Adhesive strength on steel	N/cm	0,80
Temperature Resistance	°C	Max 80 °C for one hour

### Storage and handling Recommendations

Recommended shelf life is 12 months, release force of unwinding is increased gradually.  
The product should be stored in a dark place at normal room temperature not below 18 °C.  
Rolls to be stored in the flat side down position and in the original packaging.  
In order to avoid negative results it is recommended to test the tape before individual application.

#### Note:

The tape is not suitable for applying to dusty, greasy or damp surfaces.

The above data are results of our experiences and we cannot guarantee for individual applications under different conditions.

Masking self adhesive tape is not harmful to skin contact but washing of hands is recommended. The tape is not intended for medical use or food industry.