

GEKO SpA

Via dell'Artigianato n° 22

62020 Sant'Angelo in Pontano (MC) – Italy

Tel + 39 0733 66 33 16 | Fax +39 0733 66 34 17

Codice Fiscale e P.IVA 00860500438

SDI: W7YVJK9 | REA MC 100692 | Cap Soc € 4.000.000,00 i.v.

Pec gekospa@pec.it | Web www.geko.net | email info@geko.net

TECHNICAL DATA SHEET – GEKO NET

ADHESIVE TAPE: GEKO NET

TYPE OF PRODUCT:	Adhesive tape in fibreglass
	Excellent resistance to ALKALINE
	Acrylic resin adhesive up to 60°C

Technical Data:	Average weight	≥ 75g/m2
	Mesh Size:	9 x 9 count /25mm
	Alkaline resistant acrilic adhesive	30%
	Tensile strength at breaking point:	WARP: 500N/50mm WEFT: 800N/50mm

Recommended applications:	For covering large cracks in walls and for joining plasterboards.
---------------------------	---

Storage:	For the best results it is recommended to use and store the goods in a place of low humidity and at a temperature of not less than 18°C
----------	---

The above results are taken as the average of our standard production and therefore do not constitute a binding contract on the part of GEKO SpA. The end user in any case must through practical trials ascertain the suitability of the product in various conditions, assuming any risk and responsibility derived from the same use. The above values could be changes at any moment because of any change in production or updated techniques.

Rev 4: 12/2023