

Voltage and continuity testers

PAN MV-1000AD

Voltage Tester 1000V LED + LCD + rotary field indication

- Low voltages up to 24 V: green LEDs, dangerous voltages from 50 V: red LEDs
- Analog LED and backlit digital LCD display
- **2-pole rotary field indication**
- Single pole phase test with acoustic indication
- Data Hold
- **30 mA RCD test**
- **Switchable load for suppressing stray voltages**
- **LED flashlight**
- Auto power off
- **Water and dust protection class IP 64**
- **TÜV GS tested**

Scope of delivery: screw-contact sleeves for perfect contact in sockets, Operating manual



Technical Data	PAN MV-1000AD
Measuring category (CAT)	CAT III 1000 V / CAT IV 600 V
Weight (gross / net)	432 / 263 g
AC voltage (V ~)	12 - 24 - 50 - 120 - 230 - 400 - 690 - 1000 V
DC voltage (V =)	12 - 24 - 50 - 120 - 230 - 400 - 690 - 1000 V
Resistance (Ω)	1 Ω - 1999 Ω
Continuity test (•)))	< 400 k Ω
Accuracy (%)	3,0 % - 5,0 %
Dimensions	260 x 74 x 34 mm
Required battery(s):	2x 1,5V AAA



PAN MV-1000AD Video DE:



PAN MV-1000AD Video EN:

