

## ANAFGROUP

# **SAFETY DATA SHEET**

# AEROSOL DISPENSER FOR FIRE EXTINGUISHING PURPOSES, AD6-A/C

Issued on 11/06/2015 - Rel. # 2 on 02/01/2016

Pag. 1 / 11

In conformity to Regulation (EU) 2015/830

# SECTION1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product code: AEROSOL DISPENSER FOR FIRE EXTINGUISHING PURPOSES, AD6-A/C

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Fire estinguish.

Sectors of use: Private households (= general public = consumers)[SU21], Public domain (administration, education,

entertainment, services, craftsmen)[SU22]

Uses advised against: Do not use for purposes other than those listed

### 1.3. Details of the supplier of the safety data sheet

ANAF FIRE PROTECTION S.P.A. Via del Commercio, 4 27020 Torre d'Isola Tel. 0039 (0)382 45 33 Fax: 0039 (0)382 92 02 79

e-mail: info@anaf.eu Internet: www.anaf.eu

## 1.4. Emergency telephone number

Ing. Danilo Romano Tel. 0039 (0)382 45 33

## **SECTION2.** Hazards identification

# 2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

None

Hazard Class and Category Code(s):

Aerosol

Hazard statement Code(s):

H229 - Pressurised container: May burst if heated.

The repeated inhalation of vapors can cause drowsiness and giddiness.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.



# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 2 / 11

In conformity to Regulation (EU) 2015/830

### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):

- Warning

Hazard statement Code(s):

H229 - Pressurised container: May burst if heated.

Supplemental Hazard statement Code(s):

not applicable

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 - Do not pierce or burn, even after use.

Storage

P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

Content of VOC ready to use condition: 0,66 %

## 2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

# **SECTION3. Composition/information on ingredients**

# 3.1 Substances

Irrilevant

## 3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

| Substance                 | Concentration | Classification     | Identificativi  |
|---------------------------|---------------|--------------------|---|
| 2-(2-BUTOXYETHOXY)ETHANOL | > 0,1 <= 1%   | Eye Irrit. 2, H319 | CE 603-096-00-8<br>CAS 112-34-5<br>EINECS 203-961-6<br>REACH 01-2119475104-44 |

## **SECTION4. First aid measures**

# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 3 / 11

In conformity to Regulation (EU) 2015/830

## 4.1. Description of first aid measures

#### Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product).:

Wash thoroughly with soap and running water.

Direct contact with eyes (of the pure product).:

Wash immediately and thorougly with running water for at least 10 minutes.

#### Ingestion:

It's possible to give activated charcoal in water or liquid paraffin medicine

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

## **SECTION5. Firefighting measures**

### 5.1. Extinguishing media

Irrelevant

## 5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

# 5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

## **SECTION6.** Accidental release measures



# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 4 / 11

In conformity to Regulation (EU) 2015/830

## 6.1. Personal precautions, protective equipment and emergency procedures

## 6.1.1 For non-emergency personnel:

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance. Wear gloves and protective clothing

### 6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing

Evacuate the danger area and, in case, consult an expert.

### 6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

# 6.3. Methods and material for containment and cleaning up

## 6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

#### 6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

## 6.3.3 Other information:

None in particular.

# 6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

## **SECTION7.** Handling and storage

# 7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Use extreme caution when handling the product. Avoid shock or friction.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

See also paragraph 8 below.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.



# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 5 / 11

In conformity to Regulation (EU) 2015/830

## 7.3. Specific end use(s)

Follow the rules of good hygiene in the workplace.

# SECTION8. Exposure controls/personal protection

#### 8.1. Control parameters

Related to contained substances: 2-(2-BUTOXYETHOXY)ETHANOL:

TLV-TWA: 10ppm; 67,5mg/m3 (2006/15/EC). TLV-STEL: 15ppm; 101,2mg/m3 (2006/15/EC).

MAK: 100 mg/m3 peak limitation category: I (1) Pregnancy risk group: C (DFG 2003).

- Substance: 2-(2-BUTOXYETHOXY)ETHANOL

**DNEL** 

Systemic effects Long term Workers inhalation = 67,5 (mg/m3) Systemic effects Long term Workers dermal = 20 (mg/kg bw/day) Systemic effects Long term Consumers inhalation = 34 (mg/m3) Systemic effects Long term Consumers dermal = 10 (mg/kg bw/day) Systemic effects Short term Consumers oral = 1,25 (mg/kg bw/day) Local effects Long term Workers inhalation = 67,5 Local effects Long term Consumers inhalation = 34 (mg/m3) Local effects Short term Consumers inhalation = 50,6 (mg/m3)

**PNEC** Sweet water = 1 (mg/I)sediment Sweet water = 4 (mg/kg/sediment) Sea water = 0.1 (mg/I)sediment Sea water = 0,4 (mg/kg/sediment) intermittent emissions = 3,9 (mg/l)

STP = 200 (mg/l)ground = 0,4 (mg/kg ground)

#### 8.2. Exposure controls







Appropriate engineering controls:

Observe the safety measures used in handling chemicals.

Individual protection measures:

a) Eye / face protection

When handling the pure product use safety glasses (spectacles cage) (EN 166).

b) Skin protection

i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3)

#### ANAFGROUP

# **AEROSOL SPEGNIFUOCO AD6-A/C**

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 6 / 11

In conformity to Regulation (EU) 2015/830

ii) Other

When handling the pure product wear full protective skin clothing. Better is to use cotton antistatic clothing

c) Respiratory protection

Work in a sufficiently ventilated to avoid inhaling the product.

d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

# **SECTION9. Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

| Physical and chemical properties             | Value          |
|--|----------------|
| Appearance                                   | Spray          |
| Odour  | Not applicable |
| Odour threshold                              | Undefined      |
| рН   | Undefined      |
| Melting point/freezing point                 | Undefined      |
| Initial boiling point and boiling range      | Undefined      |
| Flash point                                  | Undefined      |
| Evaporation rate                             | Undefined      |
| Flammability (solid, gas)                    | Undefined      |
| Upper/lower flammability or explosive limits | Undefined      |
| Vapour pressure                              | Undefined      |
| Vapour density                               | Undefined      |
| Relative density                             | Undefined      |
| Solubility                                   | Undefined      |
| Water solubility                             | Undefined      |
| Partition coefficient: n-octanol/water       | Undefined      |
| Auto-ignition temperature                    | Undefined      |
| Decomposition temperature                    | Undefined      |
| Viscosity                                    | Undefined      |
| Explosive properties                         | Undefined      |
| Oxidising properties                         | Undefined      |
| Container volume                             | 1000cc         |
| Product volume                               | 600cc          |
| Pressure to 20°C                             | 11bar          |
| Deformation pressure                         | Not determined |
| Burst pressure of the container              | Not determined |
| Flash point of liquid phase                  | Irrelevant     |

# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 7 / 11

In conformity to Regulation (EU) 2015/830

| Physical and chemical properties | Value      |
|----------------------------------|------------|
| Propellent inflammability        | Irrelevant |

### 9.2. Other information

Content of VOC ready to use condition: 0,66 %

# SECTION10. Stability and reactivity

## 10.1. Reactivity

No reactivity hazards

## 10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

### 10.3. Possibility of hazardous reactions

There are no hazardous reactions

### 10.4. Conditions to avoid

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 ° C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

## 10.5. Incompatible materials

None in particular.

## 10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

## **SECTION11. Toxicological information**

# 11.1. Information on toxicological effects

ATE(mix) oral = ∞ ATE(mix) dermal = ∞

ATE(mix) inhal =  $\infty$ 

(a) acute toxicity: 2-(2-BUTOXYETHOXY)ETHANOL: Acute hazards/symptoms;

# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 8 / 11

In conformity to Regulation (EU) 2015/830

Skin: dry scalp.

Eye: Eye Redness. Pain.

- (b) skin corrosion/irritation2-(2-BUTOXYETHOXY)ETHANOL: Irritating.
- (c) serious eye damage/irritation: based on available data, the classification criteria are not met.
- (d) respiratory or skin sensitization: based on available data, the classification criteria are not met.
- (e) germ cell mutagenicity: based on available data, the classification criteria are not met.
- (f) carcinogenicity: based on available data, the classification criteria are not met.
- (g) reproductive toxicity: based on available data, the classification criteria are not met.
- (h) specific target organ toxicity (STOT) single exposure: 2-(2-BUTOXYETHOXY)ETHANOL: The substance 'irritating to eyes
- (i) specific target organ toxicity (STOT) repeated exposure: based on available data, the classification criteria are not met.
  - (j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

2-(2-BUTOXYETHOXY)ETHANOL:

A harmful contamination of air sar reached slowly for evaporation of this substance at 20°C; However, for spraying or scattering, much more quickly.

The liquid degreasing the skin features.

LD50 (rat) Oral (mg/kg body weight) = 2410

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2764

## **SECTION12.** Ecological information

### 12.1. Toxicity

Related to contained substances: 2-(2-BUTOXYETHOXY)ETHANOL: Toxic for fish:

LD50 (83d) = 1300mg/L Toxic to invertebrates:

EC50 (48 h) = 100 mg/L (Daphnia magna)

Toxic for algae:

EC50 (192h) = 53mg/L

 $C(E)L\dot{5}0 \text{ (mg/I)} = 100$ 

Use according to good working practices to avoid pollution into the environment.

## 12.2. Persistence and degradability

Related to contained substances:

2-(2-BUTOXYETHOXY)ETHANOL:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

### 12.3. Bioaccumulative potential

No data available.

ANAFGROUP

# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 9 / 11

In conformity to Regulation (EU) 2015/830

## 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

### 12.6. Other adverse effects

No adverse effects

# **SECTION13. Disposal considerations**

#### 13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 ° C can burst.

Recover if possible. Operate according to local or national regulations

# **SECTION14. Transport information**

# 14.1. UN number

1950



## 14.2. UN proper shipping name

AEROSOL asphyxiant

## 14.3. Transport hazard class(es)

Class: 2 Label: 2.2

Tunnel restriction code : E Limited quantities : 1 L EmS : F-D, S-U

# 14.4. Packing group

\_\_

## 14.5. Environmental hazards

Product is not environmentally hazardous Marine polluting agent : Not



# AEROSOL SPEGNIFUOCO AD6-A/C

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 10 / 11

In conformity to Regulation (EU) 2015/830

## 14.6. Special precautions for user

The goods must be transported by vehicles authorized to transport of dangerous goods according to the current edition of ADR requirements and applicable national regulations.

The goods must be in original packing, however, in packaging made of materials resistant to their content and not likely to generate with this dangerous reactions. People loading and unloading dangerous goods must be trained on the risks from these substances and that must be taken in case of emergency situations

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

# **SECTION15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg (EC) n. 1907/2006 (REACH), Reg (EC) n. 1272/2008 (CLP), Reg (EC) n. 453/2010 (Requirements for the compilation of safety data sheets), Reg (E) n.790/2009, Dir 96/82/EC as amended.

# 15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

## **SECTION16. Other information**

### 16.1. Other information

Description of the hazard statements exposed to point 3 H319 = Causes serious eye irritation.

Classification based on data of all mixture components

Regulatory information: Dir 67/548 29° Amendment Dir 1999/45/EC e s.a.a. Dir 2001/60/EC Reg 1907/2006 EC Reg 1272/2008 EC Reg 453/2010 EC

#### NOTICE TO USERS

The information contained in this sheet are based on the knowledge available at the date of the preparation of this sheet.

The user must be aware of the possible risks associated with the use of the product, other than that for which the product is supplied. The sheet does not exonerate the user from knowing and applying all the regulations governing its activities. The set of regulations mentioned is simply to help the user to fulfill its obligations regarding the use of hazardous products.

This sheet does not exonerate the user from other legal obligations than those mentioned and from rules regulating



# **AEROSOL SPEGNIFUOCO AD6-A/C**

Issued on 11/06/2015 - Rel. # 1 on 11/06/2015

Pag. 11 / 11

In conformity to Regulation (EU) 2015/830

possession and use of the product, since the user is the only responsible.

\*\*\* This sheet supersedes all previous editions.