



Certificate according to DIN EN 10204

item number 01655 Quality NdFeB N35

Magnetic and material specific Characteristics

maximum energy product	(BH)max	≥	263	kJ/m³	Measuring	Hystograph Brockhaus BTC 200 with solenoid TJH 15
remanence	Br	≥	1170	mT		
coercitive field strength flux density	HcB	≥	868	kA/m		
coercitive field strength polarisation	HcJ	≥	955	kA/m		
temperature of application			80	°C	Measuring	manually
density			7,4	g/cm³		
flux density over air gap			340	mT	Measuring	MagScan 3D-Field measuring device
dimension	Diameter 1		20,00	mm	Measuring	digital slide gauge with data output (Mahr 16EX) steal measure
	height 1		5,00	mm		
magnetizing	kind		axially		Measuring	Fluxx foil
coating			Ni		Test	optically
minimum bending diameter (along/across)					Test	optically
					Test	manually
chemical composition					corresponds to following norms and regulation	
Nd & Pr	33,0%				DIN ISO EN 71-3	
Fe	63,9 - 68,8%				EU 2000/53/EG	
B	1 - 1,2%				EU 2002/95/EG	
Dy	1,5 - 2,5%				EU 2005/84EG	
Pb	2 ppm				EG 1907/2006 (REACH)	

Others According to the waste key EAK (Europ. Waste Catalogue) 060316 magnetic foil belongs to metal oxides with content of plastic and can, in accordance with the local waste regulations, generally be disposed of with normal household waste.

State 03.02.2025

This data sheet was prepared by EDV and it is valid without a signature

QD Rheinmagnet Horst Baermann GmbH