


Designation IEC:
HR6

Size:.....	AA
Nominal Voltage:.....	1.2 V
Rated Capacity:.....	2100 mAh
Internal Resistance DC; fully charged:.....	45 mΩ
Impedance AC at 1 kHz; fully charged:.....	40 mΩ
Max. Discharge Current (continuous load / 0.8 V):.....	4.2 A

Typical Capacity at:

0.2 C / 1.0 V:.....	2100 mAh
1.0 C / 0.9 V:.....	1890 mAh

Charge Retention:

75 % of initial capacity after one year storage at 20 °C;
determined at 0.2 C discharge rate

Dimensions:

Diameter	a:.....	14.5 ^{-1.0} mm
Height	b:.....	50.5 ^{-1.3} mm
Shoulder Height	c:.....	49.5 ^{-1.3} mm
Cap Diameter	d:.....	5.5 ^{-1.3} mm
Volume:.....		8 cm³
Weight (approx.):.....		30 g

Charge Conditions at:

Standard Charge:.....	210 mA, 16 h
Fast Charge:.....	2100 mA (-dV)
Trickle Charge (0.03 - 0.05 C):.....	63 - 105 mA

Temperatures (recommended / permissible) at:

Storage:.....	-20 °C ... 25 °C / -20 °C ... 40 °C
Charge:.....	15 °C ... 30 °C / 0 °C ... 45 °C
Fast Charge:.....	15 °C ... 30 °C / 0 °C ... 40 °C
Discharge:.....	0 °C ... 40 °C / 0 °C ... 50 °C

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries