

Sikaflex® Construction Purform®

Declaration of Performance No 99682186

1	Unique identification code of the product-type:	99682186
2	Intended use/es:	For uses subject to reaction to fire regulations — Sealants for non-structural use in joints in buildings Outdoor (exterior) applications — Sealants for external perimeter wall, window and door joints (facade elements)
3	Manufacturer:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	System/s of AVCP:	System 3 (For uses subject to reaction to fire regulations) System 3 (Outdoor (exterior) applications)
6a	Harmonised standard:	EN 15651-1:2012
	Notified body/ies:	1213

7 Declared performance/s:			
Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Resistance to flow	≤ 3 mm	System 3	
Loss of volume	≤ 10 %	System 3	
Tensile properties (i.e. elongation)	No failure	System 3	
Tensile properties (i.e. secant modulus)	≤ 0.9 MPa	System 3	
Tensile properties (i.e. at maintained extension)	No failure	System 3	
Durability	Pass	System 3	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski
Function: Corporate Product Certification Manager
At Warsaw on 2024-03-13



Name: Wiktor Karpala
Function: Data Processing Specialist CTD
At Warsaw on 2024-03-13



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance



24

Sika Services AG, Zürich, Switzerland

99682186

Reaction to fire	Class E
------------------	---------

Resistance to flow	≤ 3 mm
--------------------	-------------

Loss of volume	≤ 10 %
----------------	-------------

Tensile properties (i.e. elongation)	No failure
--------------------------------------	------------

Tensile properties (i.e. secant modulus)	≤ 0.9 MPa
--	----------------

EN 15651-1:2012

1213

For uses subject to reaction to fire regulations — Sealants for non-structural use in joints in buildings
Outdoor (exterior) applications — Sealants for external perimeter wall, window and door joints (facade elements)

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sikaflex® Construction Purform®

99682186

13/03/2024 2

1009

3 / 3

BUILDING TRUST

