

Art.No.	article name
233802006	DUOversal PLUS 3=6, with illuminated switch (2-pole), with shutter, with 35° turned sockets, cable 1.4m, mountable

DUOversal Plus, 3=6, all sockets with connection option for one grounding-type plug or two euro-plugs, with illuminated switch (2-pole), with shutter, with 35° turned sockets, 52mm distance between sockets, cable H05VV-F3G1, 5mm², 1,4m, mountable, 16A, 250V~, white



Technical data		233802006
Housing shape		Rectangular
Number of socket outlets with protective contact (SCHUKO)		3
Residual current circuit breaker (RCCB)		no
With cover lid		no
Material		Plastic
Impact strength		IK00
Transparent		no
With miniature fuse		no
Number of socket outlets with earth pin		0
Number of other socket outlets		0
Number of cold device socket outlets		0
Number of USB connections		0
Number of socket outlets type Bipasso (Italy)		0
Number of socket outlets Type P11 (Italy)		0
Number of NEMA-outlets		0
Number of universal multi standard sockets		0
Number of socket outlets French standard (Type E)		0
Compatible with Apple HomeKit		no
Compatible with Google Assistant		no
Compatible with Amazon Alexa		no
Nominal current		16.00 A
Colour		White
core cross section		1.5 mm²
Halogen free		yes
Surface protection		Untreated
Length of power cord		1.4 m
With on/off switch		yes
Mains filter		no
Rotated central insert		yes
Over voltage protection		no
RAL-number (similar)		9003
Number of socket outlets CEE 7/16 (EURO)		6

Technical data		233802006
IFTTT support available	no	
Number of socket outlets Swiss standard type 13	0	
Number of socket outlets Swiss standard type 15	0	
Number of socket outlets Swiss standard type 23	0	
Number of socket outlets Swiss standard type 25	0	
Number of socket outlets Italian standard type P17	0	
Degree of protection (IP)	IP20	
Material quality	Duroplast	
NEMA designation	None	
Surface finishing	Matt	
Angle rotated central insert	35°	
Type of mains connection	Plug CEE 7/4 (type F)	
Number of socket outlets Danish standard (earthing pin)	0	
Number of socket outlets British Standard BS1363	0	
Anti-bacterial treatment	no	
Number of socket outlets Italian standard type P30	0	
Overcurrent protection	nein	
Max. connected load	3680 W	
Directly pluggable (without power cord)	nein	
Type of plug	angled	
Number of socket outlets CEE 7/1 (no protective contact)	0	
Packaging break	N	