

GEKO SpA

Via dell'Artigianato n° 22
62020 Sant'Angelo in Pontano (MC) – Italy
Tel + 39 0733 66 33 16 | Fax +39 0733 66 34 17
Codice Fiscale e P.IVA 00860500438
SDI: W7YVJK9 | REA MC 100692 | Cap Soc € 4.000.000,00 i.v.
Pec gekospa@pec.it | Web www.geko.net | email info@geko.net

TECHNICAL DATA SHEET

ADHESIVE MASKING TAPE: GEKO MSK PRO OUTDOOR

Description:

Universal Fine Line painter's masking tape features a smooth Washi paper backing and a water-based solvent-free acrylic adhesive. Provides balanced adhesion, clean paint break lines, good mechanical strength, and clean removal after prolonged exposure to UV and water.

Designed for precision indoor/outdoor paint operations in the paint and marine industries. FSC® certified masking tapes available upon request.

Applications:

Professional long-term interior/exterior masking for paint jobs in the paint and marine industry. Exterior finishes in the marine industry.

Characteristics:

Total Weight	81g/m2
Adhesive	Water based acrylic without solvents
Support	WASHI paper
Total thickness (μ)	90
Adhesion to steel (N/cm)	1,18
Tensile strength (N/cm)	31,2
Stretch at breaking point %	3,7

- Japanese Washi paper
- Sharp break lines of the paint
- Resistant to humidity and most water and solvent based paints
- 5 months outdoor UV resistance with clean removal (unpainted)
- Ideal for PVC, glass, wood, aluminium, smooth metals and Forex®
- Excellent paint anchoring

Technical information and product use

All technical information and data mentioned above are provided to the best of our knowledge based on our practical experience. The data shown refer only to average values, based on tests carried out in a conditioned laboratory and are not valid for the specification. The company reserves the right to modify or change products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guide and use. GEKO SpA. reminds the user of the products to ensure that the product is used according to the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product for the actual application under specific conditions.

Conservation and duration

Recommended storage in a dry area out of direct sunlight, temperature should range from 59°F / 15°C to 77°F / 25°C with a maximum relative humidity of 50%. The tape and jumbo roll should be used within 12 months and 6 months of shipment date, respectively. GEKO SpA. assumes no responsibility for defective material if it is not stored and used in accordance with the conditions listed above.