

GEKO SpA

Via dell'Artigianato n° 22

62020 Sant'Angelo in Pontano (MC) – Italy

Tel +39 0733 66 33 16 | Fax +39 0733 66 34 17

Codice Fiscale e P.IVA 00860500438

SDI: W7VJK9 | REA MC 100692 | Cap Soc € 4.000.000,00 i.v.

Pec gekospa@pec.it | Web www.geko.net | email info@geko.net



TECHNICAL DATA SHEET

ADHESIVE TAPE: GEKO MSK WASHI

Excellent quality Washi paper masking tape with high temperature and UV resistance. Great for internal or external use with clean removal for up to 60 days.

Excellent for reproducing straight lines on flat surfaces with a high precision. Excellent for tape on tape results with no residue left after use.

TAPE PROPERTIES

TYPE OF PAPER	IMPREGNATED CREPE PAPER
TOTAL WEIGHT (g/m ²)	80 (+/- 3)
THICKNESS (my)	95 (+/-15)
TENSILE STRENGTH MD (N/cm)	>24
ELONGATION AT BREAK MD (%)	<5

ADHESIVE PROPERTIES

TYPE OF ADHESIVE	WATER BASED ACRYLIC
COLOUR	TRANSPARENT
ADHESION TO STEEL (N/cm)	>1,3
UV RESISTANCE (DAYS)	60
TEMPERATURE RESISTANCE (°C)	80

The recommended storage conditions for this product are around 21°C and 50% relative humidity. Prior to use, carefully check that the contact surfaces are totally dry and clean from oil, grease or dust. The data stated above cannot be considered as binding by contract or by specifications. They correspond to the average values obtained from the tests carried out in conformity with AFERA norms. Tests are carried out on samples taken from our standard production. These data may vary without notice – the updated typical value sheet can be forwarded at any time.

Since many different factors influence the product's performance, we recommend testing the product by any application. We remain at your disposal for any further information or recommendations.