

GEKO SpA

Via dell'Artigianato n° 22

62020 Sant'Angelo in Pontano (MC) – Italy

Tel + 39 0733 66 33 16 | Fax +39 0733 66 34 17

Codice Fiscale e P.IVA 00860500438

SDI: W7YVJK9 | REA MC 100692 | Cap Soc € 4.000.000,00 i.v.

Pec gekospa@pec.it | Web www.geko.net | email info@geko.net

TECHNICAL DATA SHEET – GEKO FIX IN

DOUBLE SIDED TAPE: HIGH THICKNESS FOAM

Product Description

Double sided adhesive foam tape of 1mm thickness with a modified acrylic adhesive.

Liner

Double side siliconised paper - Havana

Support

100% Polyethylene foam

Adhesive

Modified acrylic

Principle applications

Suitable for all vertical indoor applications, with moderate load. Used to glue plastic, paper, cardboard, plates, gaskets on metal. Good resistance to plasticizers, oils, solvents and UV rays.

Characteristics

Adhesive with high tack, high adhesive strength and moderate shear.

Technical data (Average values)

PARAMETER	INFO	UNIT	RESULT
PEEL ADHESION ON STEEL		N/25mm	16 +/- 10%
STATIC SHEAR	1000g, 25mm ²	h	>200
APPLICATION TEMPERATURE		°C	MIN -5 MAX +40°C
MAX WORKING TEMPERATURE		°C	> 100

The product has a shelf life of 12 months if stored in the original packaging at a temperature of 21°C with relative humidity of 50%. GEKO SpA products have been developed on the basis of high quality standards, also to give good results in harsh conditions, and are regularly subjected to restrictive controls. All the information and recommendations reported in our publications are the result of theoretical and practical experiences and are provided to the best of current knowledge. They, however, do not imply any form of guarantee, either direct or implicit, even regarding the suitability of the product for a particular application nor can they be considered the basis for technical specifications. Therefore, determining whether the GEKO SpA product is suitable for a specific application or the application techniques adopted is the responsibility of the end user.