

GEKO SpA

Via dell'Artigianato n° 22
62020 Sant'Angelo in Pontano (MC) – Italy
Tel + 39 0733 66 33 16 | Fax +39 0733 66 34 17
Codice Fiscale e P.IVA 00860500438
SDI: W7YVJK9 | REA MC 100692 | Cap Soc € 4.000.000,00 i.v.
Pec gekospa@pec.it | Web www.geko.net | email info@geko.net



TECHNICAL DATA SHEET – GEKO ALUTAPE

ADHESIVE TAPE: GEKO ALUMINIUM TAPE 30µm

Advantages and benefits

Excellent adhesion to most surfaces
Conforms to any surface
High thermal conduction
Waterproof for internal and external use
Resistant to UV rays

Typical Applications

Seals air conditioning tubes or
Pipe insulation in refrigeration and heating industry

Construction

Overall Grade: General purpose
Backing: Aluminium 30µm
Liner: White siliconised paper
Adhesive: High quality acrylic

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	65	µm	AFERA 4006
Adhesion to steel	600	cN/cm	AFERA 4001
Application range	+10 to +40	°C	
Useful temperature range	-30 to +120	°C	

The above results are taken as the average of our standard production and therefore do not constitute a binding contract on the part of GEKO SpA. The end user in any case must through practical trials ascertain the suitability of the product in various conditions, assuming any risk and responsibility derived from the same use. The above values could be changes at any moment because of a change in production or updated techniques.

Storage and Usage conditions

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.