

# THORGEON

## LIGHTING



LED 3030 LUMILEDS  
PHILIPS XITANIUM DALI DRIVE

## LED FLOODLIGHT

MODEL	EAN CODE	LED POWER	LUMENS	DIMENSIONS (mm)	WEIGHT(Kg)
03074	 4 751029 897107	150W	21000LM	317 x 469 x 65	4.5
03075	 4 751029 897114	200W	28000LM	369 x 529 x 65	6.7
03076	 4 751029 897121	300W	42000LM	399 x 611 x 79	8.49



## LED FLOODLIGHT

MODEL No: 03074, 03075, 03076

### APPLICATIONS

- Residential areas
- Buildings
- Courtyards
- Billboards

### PRODUCT FEATURES

This product is with elegant appearance and high efficiency, high configuration, long lifespan and also high temperature resistance. Various optics for options. Incremental 30deg tick marks are provided in the casting of a single hex head bolt to allow for precise aiming and to facilitate the alignment of multiple luminaires. Changeable lens available to reduce inventory cost. With gasket-fixed tempered glass. Variety of mounting accessories are provided to complement the luminaires. whether wall mounted, ceiling mounted, pole mounted or ground mounted, all aid to blend into the surroundings with different actual needs.



### TECHNICAL PARAMETERS

LED TYPE:	LUMILEDS	THD:	≤10%
LIGHT EFFICACY:	140LM/W	SURGE PROTECTION:	100W/300W: 4KV; 200W: 6KV
COLOR TEMPERATURE:	4000K	LIGHT DISTRIBUTION CURVE	60 DEG 
CRI:	70	PROTECTION CLASS IEC:	CLASS I
LED LIFESPAN:	50000@L70/B10	IP RATING:	IP66
POWER SUPPLY:	PHILIPS	IMPACT PROTECTION RATING (IK)	IK08
TYPE OF DRIVER:	CONSTANT DRIVER	OPERATING TEMPERATURE:	-30°C-+45°C
DRIVER EFFICIENCY:	RA ≥90%	STRUCTURE MATERIAL:	DIE-CASTING
CONTROLS AND DIMMING:	DIMMABLE	BRACKET:	SPCC
INTELLIGENT CONTROL:	1-10V DIMMING CONTROL	FINISH MATERIAL:	POWDER COATED
INPUT VOLTAGE:	PHILIPS: 220-240VAC;	LENS MATERIAL:	PC
INPUT FREQUENCY:	50/60HZ	FIXTURE COLOR:	DARK GRAY
		CERTIFICATE:	CE, ROHS, CB, ENEC
		WARRANTY	5 YEARS WARRANTY

