



Consumer Business Group

Construction & Home Improvement Markets

Product Information Sheet

Scotch® Extremium Ultra Strength duct tape



General description

Scotch® Extremium Ultra duct tape is a super thick tape for super tough jobs. It is ultra thick with a waterproof backing which resists moisture. It stands up to extreme conditions, both interior and exterior. It can be used for permanent repairs, patching and protecting. Its aggressive, natural rubber adhesive grips instantly to a variety of surfaces including metal, glass, plastic and sealed concrete.

Product Characteristic	Typical Value*	Test method
Backing	Polyethylene	-
Adhesive	Natural and synthetic rubber	-
Standard roll length	48mm x 25m and 24mm x 10m	-
Color	Charcoal grey	-
Total thickness	430 µm	ASTM D-3652
Adhesion to Steel	10 N/cm	ASTM D-3330
Tensile Strength	80 N/cm	ASTM D-3759
Elongation at break	24 %	ASTM D-3759
Temperature resistance	0°C to 93°C	Internal

*These are average values. 3M does not guarantee every product will have these specific test values. Actual values may vary and may be greater than or less than the averages listed.

Key benefit

Ultra strong duct tape for extreme repairs.

Storage

To obtain best performances, store this product under normal condition of 21°C and 50% relative humidity in the original packaging and use it within one year from date of purchase.

Features	Advantages	Benefits
Rubber adhesive	Instant adhesion	Sticks easily to the surface
	Very Good holding power Long lasting	Helps resist lifting or curling, holds in many applications with strength constraints
PE over cloth scrim	Hand tearable in both direction	Easy handling
	Very narrow scrim	Very high resistance
	2 times thicker than other standard 3M duct tapes	Strong holding power and high resistance
	High tensile strength	For demanding applications

Warning

Apply above 5°C and up to 40°C. Do not use on wallpaper or other delicate surfaces. Do not use on poorly bonded surfaces. In case of doubt, test before use. Do not use on flues, chimneys, mufflers or tailpipes.



3M and Scotch are trademarks of 3M Company.

IMPORTANT NOTICE: All statements, technical information and recommendations herein are based on tests and studies 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations. Before any use, it is always recommended to read and follow the instructions for use and to conduct tests to validate the adequacy of the product with regard to the envisaged use. Any action or use of the product made in breach of these indications is at the risks of the user and consequently 3M cannot be held responsible for whatever negative consequences may arise out of or in connection with any breach of the given instructions and indications. Compliance with 3M instructions for use and other recommendations does not exempt the user from respecting other local applicable rules (safety rules, standards and procedures) governing the use of the concerned product in specific contexts and/or through specific means or tools.

Limitation of Liability: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective or to return the purchase price. Statements or recommendations not contained herein shall not have any force or effect unless included in an agreement signed by a 3M officer.

3M reserves the right to amend the whole or part of this document at any time, without notice.

Terms and Conditions of product warranty are set forth in contractual documents of sale and subject to mandatory applicable laws.