



Consumer Business Group
Construction & Home Improvement Markets
Product Information Sheet

Scotch® Self Bonding Tape



General description

Scotch® Self Bonding tape is a repair tape ideal for tubes, pipes and drains temporary repairs. It can be used inside and outside.

Product Characteristic	Typical Value*	Test method
Backing	Self-fusing ethylene-polypropylene rubber	-
Standard roll length	25 mm x 1 m and 25 mm x 3 m	-
Color	Black	-
Total thickness	750 µm	AFERA 5006
Elongation at break	650 %	AFERA 5004
Operating temperature	-40°C to 90°C	Internal

*These are average values. 3M does not guarantee every product will have these specific test values. Actual values may vary and may be greater than or less than the averages listed.

Key benefit

Great elongation to adapt to all types of tubes and shapes.

Storage

To obtain best performances, store this product under normal condition of 21°C and 50% relative humidity in the original packaging and use it within one year from date of purchase.

Application

- Remove dust and grease from the surface that leaks.
- Pull out 5 to 10 cm of tape. Begin wrapping the tape completely over itself 5 to 7 cm before the repair.
- Continue to stretch and wrap using a 1 cm overlap.
- When the desired wrap is achieved, pull out 5 to 10 cm of tape.
- Wrap the final piece of tape completely over itself.

Warning

This is not an adhesive tape.

Do not use on flues, chimneys, mufflers or tailpipes.

Tightness is not guaranteed under high water pressure.

3M and Scotch are trademarks of 3M Company.

IMPORTANT NOTICE: All statements, technical information and recommendations herein are based on tests and studies 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations. Before any use, it is always recommended to read and follow the instructions for use and to conduct tests to validate the adequacy of the product with regard to the envisaged use. Any action or use of the product made in breach of these indications is at the risks of the user and consequently 3M cannot be held responsible for whatever negative consequences may arise out of or in connection with any breach of the given instructions and indications. Compliance with 3M instructions for use and other recommendations does not exempt the user from respecting other local applicable rules (safety rules, standards and procedures) governing the use of the concerned product in specific contexts and/or through specific means or tools.

Limitation of Liability: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective or to return the purchase price. Statements or recommendations not contained herein shall not have any force or effect unless included in an agreement signed by a 3M officer.

3M reserves the right to amend the whole or part of this document at any time, without notice.

Terms and Conditions of product warranty are set forth in contractual documents of sale and subject to mandatory applicable laws.