



METALGRUPSA



Codos soldar

Código	A	B	C	D	E
201110	10	3/8"	21.5	25	24
112	12	3/8"	21.5	25	24
114	14	3/8"	21.5	27	27
115	15	3/8"	21.5	28	27
210	10	1/2"	26.5	31	29
212	12	1/2"	26.5	31.5	29.5
214	14	1/2"	26.5	31.5	29
215	15	1/2"	26.5	32	29.5
225	15	1/2"	25.7	28	28.5
216	16	1/2"	26.5	32.5	29
218	18	1/2"	26.5	33	33.5
222	22	1/2"	30	36.5	39.5
314	14	3/4"	33	33.7	31
315	15	3/4"	33	33.7	31
316	16	3/4"	33	33.7	31
318	18	3/4"	33	33.2	40
322	22	3/4"	33	37	43
328	28	3/4"	34	41.5	47.8
422	22	1"	40	47	42
428	28	1"	40	52.5	50.5
528	28	1 1/4"	50	47	42
535	35	1 1/4"	50	60	64.5
642	42	1 1/2"	56	74	78.5
754	54	2"	69	83	95.5

(Medidas orientativas sin valor contractual)

Dimensiones según EN 1254 – 4

Material: CW617N

PN 20

Temp. Max: 110°C

Dpto Técnico calidad
Mars Rodríguez

