



-Racor Marsella Reducción M-H  
-Hexagonal Reducing Bushing M-F

CODG / CODE	A	B	C	D	E	F	G
353334	1/8"	3/4"	7	---	17.5	9.5	E/C 15.9
353441	1/4"	3/8"	8	---	21	10	E/C 18.9
353102	3/8"	1/2"	8.5	Ø26	20.25	10.5	E/C 22.9
353122	3/8"	1/2"	7.5	Ø18	18	8.5	E/C 22.9
353103	3/8"	3/4"	10	Ø33	24	11	E/C 28.9
353255	5/8"	1/2"	11.5	Ø29	26	12	E/C 24.9
353203	1/2"	3/4"	10.5	Ø335	24.5	12	E/C 28.9
353204	1/2"	1"	9.5	Ø42	26.5	14	E/C 35.9
353205	1/2"	1"-1/4	13	Ø52.5	31	14.5	E/C 45.9
353304	3/4"	1"	12.5	Ø41.5	30	15	E/C 35.9
353305	3/4"	1"-1/4	11	Ø53	29.5	16	E/C 45.9
353307	3/4"	2"	13	Ø76	36.5	19.5	E/C 64.9
353405	1"	1"-1/4	12.5	Ø53	31	16	E/C 45.9
353406	1"	1"-1/2	12.5	Ø61	33	18	E/C 51.9
353407	1"	2"	16	Ø75.5	39	19.5	E/C 64.4
353506	1"-1/4	1"-1/2	16	Ø61	36.5	18	E/C 51.9
353507	1"-1/4	2"	16	Ø76	39.5	20.5	E/C 64.9
353607	1"-1/2	2"	18	Ø76	41.5	20.5	E/C 64.9
353708	2"	2"-1/2	18	Ø91	45	24	E/C 79.9

(Medidas orientativas sin valor contractual)  
(Indicative measures without contractual value)

Dimensiones según EN 1254-4

Dimensions according EN 1254-4

Material: CW617N

Raw material: CW617N

PN 25

NP 25

Temp. Max: 160°C

Max. Temp: 160°C

Dpto. Técnico y Calidad  
Technical department & quality  
Sr. Marc Rodríguez