



Cat.6 RJ45 Modular Plug, STP

Art no.: MP0077

Technical Features

Shielded RJ45 plug for Cat.6 Cable

Easy assembling


Inserts the wires right through the connector

Eliminates loading bar and liners

For solid & stranded wire AWG24-27

Max. cable diameter: 4.8 - 6.5mm

Technical Drawings



Electrical Characteristics:

a. Electrical

1. Voltage Rating: 150 VAC RMS
2. Current Rating: 1.5 AMP
3. Contact Resistance: 20MΩ max.
4. Insulation Resistance: 1000MΩ min. 500V DC
5. 1000V DC or AC Peak, one contact to all other contacts connected together; 1500 DC or AC Peak; all contacts connected together to shield, (Housing/Mounting Plate) if present. @ 0.5MA 50HZ or 60HZ a minute

b. Mechanical

1. Retention Strength: 50N min. for 60S±5S
2. Operating Life: 750 Cycles
3. Insertion Force: 30N max.

c. Environmental

1. Operating Temperature: -25°C~50°C
2. Storage Temperature: -25°C~50°C, Relative humidity: <80°C

- d. Plug will accept 23 or 24AWG solid cable a maximum insulation diameter of 0.97-1.07mm and a maximum diameter cable jacket of 5.8mm

MP0077



4 052792 061604

Made in China

www.logilink.com



RoHS
compliant




*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

Package Contents

50 x Cat.6 RJ45 Modular Plug

Packaging Informations

Packing Dimension	120x170mm
Packing Weight	0.1kg
Carton Dimension	550x400x350mm
Carton Q'ty	100pcs
Carton Weight	11.6kg



MP0077



Made in China

www.logilink.com



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.