

3M Construction & Home Improvement Markets

Product Information Sheet

Issue : November 2022

Supersedes: Dec 2021

Command® Adhesive: Outdoor and Bath Strips



General Description

Command™ Outdoor Adhesive is a high performance pressure sensitive tape designed with a unique, stretchable backing which allows clean, damage-free removal from most surfaces while having strong holding power in outdoor environments, including hot and cold temperatures, and in conditions with humidity or UV exposure. The adhesive strips are quick and easy to install without tools.

The strips come in multiple sizes and can be paired with Command™ hard good items including hooks, hangers, caddies, and clips that are designed for use in both bath and outdoor decorating applications.

Strip Construction

	Light Blue Strip	Clear Strip
Foam Type	Polyethylene Foam	Polyethylene Film
Adhesive Type	Silicone	Silicone
Average Thickness (Adhesive Strip without paper liners)	0.9 mm	0.36 mm
Color	Light Blue	Clear, colorless
Release Liner	0.1 mm, white paper with red and black print	0.1 mm, white paper with blue and black print
Approximate Foam Density	96 kg/m ³	


Typical Physical Properties and Performance Characteristics

Static Shear Strength (ASTM D-3654)	1000 g at 22°C
Temperature Resistance	-29°C to 50°C
U.V. Resistance	U.V. Resistant
Storage Conditions	Store under normal conditions of 16° to 27°C and 40 to 60% relative humidity in the original packaging

The values displayed are the result of illustrative lab test measures made according to the indicated test method and shall not be considered as a commitment from 3M

Available Sizes

	Strips width & length	Tab length	Adhesive width & length (wall side)	Adhesive width & length (object side)
Large	1.9 X 9.27 cm	1.9 cm	1.9 X 7.36 cm	1.9 X 6.85 cm
Medium	1.58 x 6.98 cm	1.9 cm	1.58 X 5.08 cm	1.58 X 4.56 cm
Small	1.58 x 4.6 cm	1.9 cm	1.58 x 2.69 cm	1.58 X 2.17 cm
Mini	1.27 x 2.99 cm	1.4 cm	1.27 X 1.55 cm	1.27 X 1.55 cm



<u>Feature</u>	<u>Advantage</u>	<u>Benefit</u>
Pressure-Sensitive Adhesive Strips	High adhesion	Excellent holding power
	Broad adhesion	Adheres to a wide variety of surfaces
	Quick and easy to install	No tools required
Stretch-Release Technology	Easy removal	Removes cleanly from most surfaces without damage
Foam Backing	Conformable	Adheres to both smooth and semi-rough surfaces
Film Backing	Clear	Transparent and inconspicuous appearance on most surfaces
	Thin	Ideal for low profile mounting
Silicone Adhesive	Water Resistance	Allows for use in wet or humid environments
	Temperature Resistance	Allows for use in more extreme cold and hot temperatures
Hooks, Clips, Organizers, Accessories	Molded plastic utility and decorative styles	Designed to hold items ranging in weight from 3.0 – 7.5 lbs.
Outdoor Hooks and Clips	Utility and decorative styles with UV resistance	Designed to hold items ranging in weight from 3-5 lbs.

Application and removal for bath and outdoor hooks and other similar items:

APPLY APLICAR

1 Choose a location where strips are not over grout lines. Elija un lugar en el cual las tiras no queden colocadas sobre las líneas de juntas.

2 Clean surface with rubbing alcohol. Do not use household cleaners. Limpie la superficie con alcohol isopropil. No utilice limpiadores de uso doméstico.

3 Remove blue liner. Press adhesive to hook. Retire el protector azul. Presione el adhesivo en el gancho.

4 Remove black liner. Press to wall for 10 seconds. Retire el protector negro. Presione a la pared por 10 segundos.

5 UP ARRIBA
To ensure adhesive hold, slide hook up and off. Para garantizar la sujeción adhesiva, deslice el gancho hacia arriba para sacarlo.

6 Press base firmly for 30 seconds. Presione la base firmemente por 30 segundos.

7 24 HOURS/HORAS
Use shower once and wait 24 hours to allow adhesive to build. Utilice la ducha una vez y espere 24 horas para permitir que el adhesivo aumente su poder.

8 DOWN ABAJO
Slide hook on to mounting base. Coloque el gancho de nuevo, deslizándolo hacia abajo.

REMOVE RETIRAR

1 UP ARRIBA
Slide hook up and off. Deslice el gancho hacia arriba para sacarlo.

2 Gently hold mounting base in place. Sostenga la base de montaje en su lugar.

3 Never pull the strip towards you! Always pull straight down. ¡Nunca jale la tira hacia usted! Siempre jale directamente hacia abajo.

4 Stretch the strip slowly against the wall at least 15 inches to release. Estire la tira lentamente contra la pared por lo menos 38 cm para soltar.

Application and removal clear outdoor hooks:

PREP PREPARADO

Not recommended on rough surfaces, such as cement board, brick or rough-sawn wood. No recomendado usar en superficies rugosas, como cemento, ladrillo o maderas sin terminar.

Wait 7 days after painting before use. Después de pintar espere 7 días antes de usar.

Do not hang frames on hooks. No cuelgue marcos de cuadros con ganchos.

Wipe wall with rubbing alcohol. Do not use household cleaners or water. Limpie la pared con alcohol isopropil. No utilice limpiadores de uso doméstico o agua.

APPLY APLIQUE

1 Separate strips. Remove blue liner. Press adhesive to clip. Separe las tiras. Retire el protector azul. Presione el adhesivo en el clip.

Use one clip for every 2 feet of lights. Use un clip para 60 cm de extensión de luces.

2 Remove black liner. Press firmly to a smooth, clean and dry surface for 30 seconds per clip. Retire el protector negro. Presione firmemente cada clip a una superficie lisa, limpia y seca por 30 segundos.

Wait 1 hour for adhesive to build. Espere 1 hora para que el adhesivo pegue correctamente.

REMOVE RETIRE

1 Hold clip gently in place. Sostenga el clip suavemente en su lugar.

2 Stretch the strip slowly against the wall at least 6 inches to release. Nunca jale horizontalmente de la pared. Estire la tira lentamente contra la pared por lo menos 15 cm para soltar.

Notes:

- Failure to follow instructions carefully may result in damage
- Do not use on wallpaper
- May not adhere well to vinyl surfaces
- DO NOT use for antiques, heirlooms, or other valuable or irreplaceable items
- DO NOT hang objects over beds
- Use only one hook per item hung
- Apply to surfaces above 15° F (-10° C)
- Adhesive could soften and lose adhesion above 125° F (50°C)
- Will not adhere to dirty, dusty, or oily surfaces
- Wait at least 7 days to apply to freshly painted surfaces
- Not recommended for use on bare wood or porous, unpainted surfaces
- Holding capacity is reduced if adequate pressure is not applied over 30 seconds or if the load is applied less than one hour after the adhesive has been applied
-

3M Construction and Home Improvement Markets Division
Please write your local 3M address

IMPORTANT NOTICE: All statements, technical information and recommendations herein are based on tests and studies 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations. Before any use, it is always recommended to read and follow the instructions for use and to conduct tests to validate the adequacy of the product with regard to the envisaged use. Any action or use of the product made in breach of these indications is at the risks of the user and consequently 3M cannot be held responsible for whatever negative consequences may arise out of or in connection with any breach of the given instructions and indications. Compliance with 3M instructions for use and other recommendations does not exempt the user from respecting other local applicable rules (safety rules, standards and procedures) governing the use of the concerned product in specific contexts and/or through specific means or tools.

Limitation of Liability: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective or to return the purchase price. Statements or recommendations not contained herein shall not have any force or effect unless included in an agreement signed by a 3M officer.
3M reserves the right to amend the whole or part of this document at any time, without notice.