

BM201WL, BM203WL

ROTATIVO LED
LED BEACON

Ref.:BM201WL, BM203WL

ESPECIFICACIONES TÉCNICAS TECHNICAL SPECIFICATIONS

			BM201WL	BM203WL
CONSTRUCCIÓN CONSTRUCTION	Voltaje	Voltage	DC12-24V	DC12-24V
	Consumo (A)	Draw (A)	1,6A -12V 0,8A - 24V	1,6A -12V 0,8A - 24V
	LED	LED	45	45
	Color	Color	Amber	Amber
	Tipo	Type	Base magnética + cable de resorte / <i>Magnetic Base + Spring cable</i>	Base DIN flexible / <i>Flexible DIN base</i>
	Temperatura de trabajo	Working Temperature	-30 / +50 °C	-30 / +50 °C
	Protección IP	IP protection	IP65	IP65
EMBALAJE UNITARIO SINGLE PACKING	Dimensiones (mm)	Dimensions (mm)	133 * 133 * 170	133 * 133 *210
	Peso neto (Kg)	Net weight (Kg)	0,6	0,6
	Peso bruto (Kg)	Gross weight (Kg)	0,71	0,71
EMBALAJE MASTER MASTER CARTON	Caja master (unidades)	Master carton (units)	20	20
	Dimensiones (mm)	Dimensions (mm)	750 * 310 *350	750 * 310 *420
	Peso bruto (Kg)	Gross weight (Kg)	14,2	14,2
	Código EAN	EAN Code	8434691386082	8434691386099

OTRAS CARACTERÍSTICAS OTHER SPECIFICATIONS	Funciones : Intermitente simple (R65) Intermitente doble (R65)	Functions: Single Flashing (R65) Dual Flashing (R65)
---	--	--

