

GEKO SpA

Via dell'Artigianato n° 22

62020 Sant'Angelo in Pontano (MC) – Italy

Tel + 39 0733 66 33 16 | Fax +39 0733 66 34 17

Codice Fiscale e P.IVA 00860500438

SDI: W7YVJK9 | REA MC 100692 | Cap Soc € 4.000.000,00 i.v.

Pec gekospa@pec.it | Web www.geko.net | email info@geko.net



TECHNICAL DATA SHEET – GEKO SIGIL

ADHESIVE TAPE: GEKO SIGIL

TYPE OF PRODUCT:	Adhesive tape in BOPP
	Acrylic water based adhesive

Technical Data:	Support thickness:	28µm +/- 3%
	Total thickness:	45µm +/- 6%
	Adhesion to steel:	≥ 400g/cm
	Tensile strength at break	≥ 4,2kg/cm
	Stretch at breaking point:	≤ 165%

Recommended applications:	Manual closure of packaging with friction dispenser.
	Useful for automatic dispensers

Storage:	For the best results it is recommended to use and store the goods in a place of low humidity and at a temperature of not less than 18°C
----------	---

The above results are taken as the average of our standard production and therefore do not constitute a binding contract on the part of GEKO SpA. The end user in any case must through practical trials ascertain the suitability of the product in various conditions, assuming any risk and responsibility derived from the same use. The above values could be changes at any moment because o fan change in production or updated techniques.

Test Method: AFERA – PTSC rev. 1

01/01/2013 REV 3: 12/2023