

Releasable Wire Connectors, Lever Type

- Polycarbonate and Polyamide 66, UL 94V-0 flame-retardant shell rated at T85 (IEC), 105°C/221°F (UL).
- Spring force connector constructed from tinned copper plate and stainless spring steel.
- Clear shell gives visual verification of connection.
- Accept solid and stranded conductors from 0,2 mm²/28 AWG up to 4,0 mm²/12 AWG.
- Open the clamping unit via the integrated lever, and insert conductors without using any tools.
- Rated to 600V max. for building wiring and 1000V max. in lighting fixtures/luminaires and signs.
- IEC/EN 60998 Certified and UL 486C Listed.



PC62* SERIES				
Electrical Ratings & Wire Range	32A, 450V, T85°C 0,2-4 mm², Rigid/Flexible	600V, 105°C (221°F) 28-12 AWG, Sol/Str Cu		
Approvals	CE   			
Dimensions (mm)	Cat. No.	Color	Poles	Packing
	PC622	Clear + Orange	2	Box of 100 Carton of 5,000 (10 bags, 500 ea.)
	PC623	Clear + Orange	3	Box of 100 Carton of 5,000 (10 bags, 500 ea.)
	PC625	Clear + Orange	5	Box of 50 Carton of 3,000 (10 bags, 300 ea.)

RoHS Compliant
 REACH Compliant