



|                               |                                       |
|-------------------------------|---------------------------------------|
| Type Designation              | 4703                                  |
| Designation IEC               | LR03                                  |
| System                        | Zn-MnO <sub>2</sub> (Alkaline)        |
| Shelf Life (Coding)*          | 10 years                              |
| Nominal Voltage [V]           | 1.5                                   |
| Typical Capacity C [mAh]      | 1280 (discharge with high-resistance) |
| Permissible Temperature Range | - 20 °C ... 50 °C                     |
| Weight, approx. [g]           | 11,5                                  |
| Volume [ccm]                  | 3.8                                   |

Dimensions [mm] min: max:

|   |      |      |
|---|------|------|
| Ø | 9.8  | 10.5 |
| A | -    | 44.5 |
| B | 43.5 | -    |
| C | 4.3  | -    |
| E | -    | 0.5  |
| F | -    | 3.8  |
| G | 0.8  | -    |

### Typical Capacities (at 20°C):



| Discharge Type    | Load  | End Voltage[V] | 0.9  |
|-------------------|-------|----------------|------|
| 1H/12H, 7D/W      | 50 mA | Time [h]       | 24,0 |
| Digital audio     |       | Capacity [mAh] | 1185 |
|                   |       | Energy [mWh]   | 1470 |
| Discharge Type    | Load  | End Voltage[V] | 0.9  |
| 4M/H, 8H/D, 7D/W  | 5,1 Ω | Time [min]     | 274  |
| Portable lighting |       | Capacity [mAh] | 1021 |
|                   |       | Energy [mWh]   | 1201 |
| Discharge Type    | Load  | End Voltage[V] | 0.8  |
| 1H/D 7D/W         | 5,1 Ω | Time [min]     | 287  |
| Toy               |       | Capacity [mAh] | 1060 |
|                   |       | Energy [mWh]   | 1200 |

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**

\* In consideration of typical loss of capacity at storage and application.