

TECHNICAL DATA SHEET

GEKO SOFT WHITE AND BROWN

Description Self adhesive doorbottom in soft PVC.

Characteristics of PVC

Density 400gr/m² +/- 10%
Composition 100% PVC formula
Dimensions 38MM X 100CM
Thickness 2mm +/- 0,2mm
Density liquid form 200gr/l +/-5%

Characteristics of adhesive

Type Double-sided self-adhesive tape with good initial tack and shear.
Liner Havana double sided siliconised paper
Carrier Clear TNT (polyester)
Type of Adhesive Clear water based acrylic

FEATURES

Aggressive adhesive, high tack and adhesiveness on both sides. Performs well on different materials and surfaces. Resistant to plasticizers. Medium resistance to ageing and to UV rays. Easily torn by hand

TECHNICAL DATA adhesive tape N120 (W) (average values)

ELONGATION	% ASTM D 3759	5
TENSILE STRENGTH	N/cm² ASTM D 897	2,5
ADHESION TO STEEL	N/25mm ASTM D 3330	18
THICKNESS (without liner)	μ ASTM D3652	120
NON WOVEN THICKNESS	μ ASTM D3652	20
MAX TEMPERATURE RESISTANCE	°C INTERNAL	90

Kept in its own packaging at a temperature of 23°C and relative humidity of 50%, the product has a shelf life of 12 months. Before fitting, remove every trace of dust oil and grease from the surface. The data above should not be considered a contract or specification. The data represent the average values obtained from tests carried out on samples taken from production. The information may be changed without notice - please ask the company to get the latest update. Because of the many operating conditions, we recommend that the user verifies the suitability of the product for each specific application, assuming the responsibilities arising from improper use. Our technicians are at your disposal for any clarification / advice.