

Art. 4050/4051/4052/4053/4054/4055

Gotas autoadhesivas protectoras
Self-adhesive protective buffers

MATERIAL

GOTA / BUFFER

POLIURETANO / POLYURETHANE

ADHESIVO / ADHESIVE

ACRÍLICO / ACRYLIC



COLOR / COLOUR

TODOS / ALL

100% TRANSPARENTE / CLEAR

DIMENSIONES / PRODUCT SIZE

Art. 4050	Ø8 x 2,2 mm
Art. 4051	Ø12,7 x 3,5 mm
Art. 4052	Ø16 x 7,9 mm
Art. 4053	Ø19 x 4 mm
Art. 4054	12,7 x 12,7 x 3,1 mm
Art. 4055	20,5 x 20,5 x 7,6 mm

CARACTERÍSTICAS / PRODUCT FEATURES

Dureza / Hardness	ASTM-D2240	75 Shore A
Coef. Fricción (Mk)	ASTM-D1894	Acero/Steel: >1 Madera laminada/Laminated Wood: 0,9-1,4 Vidrio/Glass: >1
Abrasión / Abrasion	ASTM-C501-66	0,13 g / 1000 cyc
Tracción / Tensile	ASTM-D412-Troquel A	5,1 MPa
Dieléctrica / Dielectric	ASTM-D1000	370 volts/mm
Temperatura de Servicio	Constante/Constant	-34°C / 66°C
Service Temperature	Puntual/Intermittent	Hasta 107°C

CARACTERÍSTICAS / PRODUCT FEATURES

Gran poder de amortiguación de golpes y vibraciones
Offers impact cushioning and noise dumping
Adhesivo de base acrílica apto para múltiples superficies
Acrylic adhesive suitable in several kind of surfaces
Antideslizante, alto coeficiente de fricción
Excellent skid resistance
No mancha ni estropea las superficies
Resistance to marring and staining



Saint Genis S.A.
Ctra. N340, km 1240 (Pol. Ind. Grab)
08758 Cervelló (Barcelona) SPAIN
Tel.: +34 93 684 05 52
info@inofix.com



Saint Genis